जयपुर विकास प्राधिकरण, जयपुर

इन्दिरा सर्किल, जे.एल.एन. मार्ग, जयपुर

क्रमांकः जविप्रा / अधि.अभि.(प्रोजेक्ट-II) / 2020-21 / डी-

दिनांक:

बिड आमंत्रण सूचना

बिड संख्या— अधि.अभि.(प्रोजेक्ट—II) / 02 / 2020—21

जयपुर विकास प्राधिकरण प्रोजेक्ट—II में "Miscellaneous Civil Work at Rajasthan International Centre, Jhalana, Jaipur" कार्य जिसकी लागत रू. 235.68 लाख के लिए दिनांक 11.08.2020 सायंकाल 6:00 बजे तक ऑन लाईन निविदायें आमंत्रित की जाती हैं। विस्तृत विवरण, जो कि निविदा प्रपत्र में उपलब्ध है, अद्योहस्ताक्षरकर्ता के कार्यालय में अथवा राजस्थान सरकार के उपापन पोर्टल www.sppp.raj.nic.in व www.eproc.rajasthan.gov.in एवं जयपुर विकास प्राधिकरण की वेबसाईट www.jda.urban.rajasthan.gov.in पर देखा जा सकता है। (UBN No.________)

निविदादाता को निविदा में भाग लेने हेतु आवश्यक है कि वह :-

- 1. जयपुर विकास प्राधिकरण की वेबसाईट www.jda.urban.rajasthan.gov.in पर पंजीकृत हो। निविदा शुल्क व आर.आई.एस.एल. प्रक्रिया शुल्क केवल ऑन लाईन ही देय होगा। बोली प्रतिभूति ऑनलाईन अथवा बैंक गारन्टी के द्वारा दी जा सकती है।
- 2. ऑन लाईन निविदा में भाग लेने हेतु राजस्थान सरकार के पोर्टल www.eproc.rajasthan.gov.in पर पंजीकृत हो।

अधिशाषी अभियन्ता (प्रोजेक्ट—II) जविप्रा, जयपुर।

JAIPUR DEVELOPMENT AUTHORITY

Room No. MB FF 106, Main Building, Ram Kishore Vyas Bhavan, Indira Circle, JawaharLal Nehru Marg, Jaipur – 302004 Telephone: +91-141-2569696 e.mail: ravindramathur2@gmail.com

Bid No:- JDA/EE(Pr.-II)/2020-21/D- Dated:

NOTICE INVITING BID

NIB No.: EE (Project-II)/02/2020-21

Online B	ids are invit	ed upt	o 6.00 PM	of 11.0	08.2020 or	"Miso	cellane	ous Civi	l Work at Ra	jasthan
Internati	ional Centre	e, Jhal	ana, Jaipu	r " Esti	mated cost	Rs. 23	35.68 L	acs. Deta	ails may be see	en in the
Bidding	Document	at o	our office	or th	e website	of	State	Public	Procurement	Portal:
www.spp	p.rajasthan.g	gov.in,	www.epro	c.rajast	han.gov.in	and w	ww.jd	la.urban.ı	rajasthan.gov.i	n (UBN
No)							

To participate in the bid, bidder has to be:

- 1. Registered on JDA website www.jda.urban.rajasthan.gov.in. For participating in the Bid, the Bidder has to apply for the Bid and pay the Bidding Document Fee & RISL Processing Fee online only and Bid Security Deposit (BSD), online or through bank guarantee.
- 2. Registered on e-Procurement Portal of Government of Rajasthan www.eproc.rajasthan.gov.in for online e-Bid submission.

(R.P. Mathur)
Executive Engineer (Project-II)
JDA, Jaipur

Dated: 10/07/2020

JAIPUR DEVELOPMENT AUTHORITY

Room No. 106, First Floor, Main Building, Ram Kishore Vyas Bhavan, Indira Circle, JawaharLal Nehru Marg, Jaipur – 302 004 Telephone: +91-141-2569696 E.mail: eeproject2jda@gmail.com

Bid No:- JDA/EE(Project-II)/2020-21/D-

NOTICE INVITING BID

NIB No.: EE (Project-II)/2020-21/02

	NIB No. : EE (Project-II)/2020-21/02
Name & Address of the Procuring	
Entity	Address: Room No. 106, First Floor, Main Building, Ram Kishore Vyas Bhavan,
	Indira Circle, JawaharLal Nehru Marg, Jaipur - 302 004
	Telephone: +91-141-2569696 E.mail: eeproject2jda@gmail.com
Subject Matter of Procurement	➤ Miscellaneous Civil Work at Rajasthan International Centre, Jhalana,
	Jaipur
	➤ Job No.: 297/2012-13 (NR-014/2019-20)
Bid Procedure	➤ Single bid open competitive E bid procedure at <u>eproc.rajasthan.gov.in</u>
Bid Evaluation Criteria (Selection	➤L1 (eg.Least Cost Based Selection (LCBS)-L1)
Method)	
Websites for downloading	➤ Websites: <u>www.sppp.rajasthan.gov.in</u> , <u>www.eproc.rajasthan.gov.in</u> ,
Bidding Document,	www.jda.urban.rajasthan.gov.in
Corrigendum's, Addendums, etc.	
Website for online Bid	➤ Website: www.jda.urban.rajasthan.gov.in
application participation and	➤ For participating in the Bid, the Bidder has to apply for this Bid and pay the
payment *	Bidding Document Fee, RISL Processing Fee and Bid Security Deposit, online
	only.
	o Bidding document fee: Rs. 1000/- Rupees (One Thousand only)
	o RISL Processing Fee: Rs. 1000/- (Rupees One Thousand only)
	Requisite Bid Security Deposit
	➤ INR 2,35,67,618/- (Rupees Two Crore Thirty Five Lacs Sixty Seven Thousand
Estimated Procurement Cost	Six Hundred Eighteen only)
Bid Security Deposit	➤ Amount (INR: *2% (Rs. 4,71,352.00/-) of Estimated Procurement Cost, 0.5%
	(Rs. 1,17,838.00/-) of S.S.I. of Rajasthan, 1% (Rs. 2,35,676.00/-) for Sick
	Industries, other than S.S.I., whose cases are pending with Board of Industrial &
	Financial Reconstruction, (*2% for Bidder who is A and AA class contractor
	registered in other Government Department / 0.5% for Bidder registered as
	contractor AA, A in JDA)
	➤ Micro Small Medium Enterprise Situated in Rajasthan Tender Fee 50% EMD Value 0.5%
	➤ In case of Departments' of the State Government and Undertakings,
	Corporations, Autonomous bodies, Registered Societies, Cooperative Societies
	which are owned or controlled or managed by the State Government and
	Government Undertakings of the Central Government shall submit a bid
	securing declaration in lieu of bid security.
Date/Time/Place of Pre-Bid	➤ NA
Applying Bid and making Online	➤ Start Date: 10.07.2020 at 9.30 AM
Payment on JDA portal	➤ End Date: 11.08.2020 at 06.00 PM
(www.jda.urban.rajasthan.gov.in)	➤ In case EMD in from BG Original Bank Guarantee is to be submitted in Room
	No MB-SF-225A (Room No. of DD (E&B) of Main Building, Jaipur
	Development Authority by 13.08.2020 10.00 AM to 13.08.2020 upto 5.00 PM
Bid Submission on e-	➤ Start Date: 10.07.2020 at 9.30 AM
Procurement Portal of GOR	➤End Date: 11.08.2020 at 06.00 PM
Date/Time/Place of Bid Opening	➤ 14.08.2020 at 11.00 AM
D. (Tr. /M. Cr.	N N T A
Date/ Time/ Place of Financial	≻NA
Bid Opening	

Bid Validity	▶120 days from the bid submission deadline
Completion period of work	▶12 Month

* Jaipur Development Authority has decided to receive Earnest Money Deposit (EMD) (Bid Security), Tender Fee and RISL processing fee online through JDA Portal. The bid security options available in tender for participants are as mentioned below:

A. Payment Options:

Option-1: Bank Guarantee (BG) against EMD / Bid Security

Bidder may opt Bank Guarantee (BG) against EMD (Bid Security), for which bidder requires to prepare BG before applying in the tender. The details of BG requires to be fed on JDA portal before paying balance amount (Tender Fee + RISL Processing Fee). This amount will be paid through Payment Gateway only, option to make balance payment through EFT (RTGS/NEFT) will not be available.

If bidder does not opt for BG against EMD, options of making complete payment through Payment Gateway or through EFT (NEFT / RTGS) will be available.

Option-2: Electronic Fund Transfer (EFT: NEFT/RTGS)

If the bidder selects payment mode as EFT (NEFT/RTGS), "Paying Slip for EFT (NEFT/RTGS)" will be generated by the system for the complete amount. The payment can be made from any Bank any Branch using this Paying Slip through NEFT/RTGS (Claim against payment made through EFT in any other JDA bank account will not be acceptable and bidder stands disqualified from participation in the bid applied for). After successful transaction through NEFT/RTGS, as per the standard procedures it may take 4 to 24 hours in process of confirmation of EFT through Auto-Process depending on the time of EFT done. Therefore, option to make payment through EFT (NEFT/RTGS) will be available till 48 hours prior to closing date of bid participation.

Option-3: Payment Gateway (Aggregator)

The facility to make payment through Debit Card, Credit Card, Net banking etc., will be available. User can use this facility from anywhere any time till the closing date & time of bid participation.

B. Bid Participation Receipt

After confirming payment, the bidder will get Bid Participation Receipt on the basis of which user will get the payment details along with other details for bidding on e-Procurement portal of GOR.

- In case of BG as the remaining payment will be done through Payment Gateway, on successful transaction the "Bid Participation Receipt" will be generated on real time basis.
- In case complete payment is done through Payment Gateway, on successful transaction the "Bid Participation Receipt" will be generated on real time basis.
- In case complete payment is done through EFT (NEFT/RTGS), on confirmation of payment from ICICI Bank (Auto Process) "Bid Participation Receipt" will be available on Login of Bidder on JDA portal.

Note:

- 1. Bidder (authorised signatory) shall submit their offer on-line in Electronic formats both for technical and financial proposal.
- 2. In case, any of the bidders fails to pay the Tender Fee, BSD, and RISL Processing Fee, online (subject to confirmation), its Bid shall not be accepted.
- 3. To participate in online bidding process, Bidders must procure a Digital Signature Certificate (Type III) as per Information Technology Act-2000 using which they can digitally sign their electronic bids. Bidders can procure the same from any CCA approved certifying agency, i.e. TCS, Safecrypt, Ncode etc. Bidders who already have a valid Digital Signature Certificate (DSC) need not procure a new DSC. Also, bidders must register on http://eproc.rajasthan.gov.in (bidders already registered on http://eproc.rajasthan.gov.in before 30-09-2011 must register again).
- 4. JDA will not be responsible for delay in online submission due to any reason. For this, bidders are requested to upload the complete bid well advance in time so as to avoid 11th hour issues like slow speed; choking of web site due to heavy load or any other unforeseen problems.
- 5. Bidders are also advised to refer "Bidders Manual Kit" available at eProc website for further details about the e-Tendering process.
- 6. Training for the bidders on the usage of e-Tendering System (eProcurement) is also being arranged by DoIT&C, GoR on a regular basis. Bidders interested for training may contact e-Procurement Cell, DoIT&C for booking the training slot.
 - Contact No: 0141-4022688 (Help desk 10 am to 6 pm on all working days) e-mail: eproc@rajasthan.gov.in Address: e-Procurement Cell, JDA, Yojana Bhawan, Tilak Marg, C-Scheme, Jaipur
- 7. The procuring entity reserves the complete right to cancel the bid process and reject any or all of the Bids.
- 8. No contractual obligation whatsoever shall arise from the bidding document/ bidding process unless and until a formal contract is signed and executed between the procuring entity and the successful bidder.
- 9. Procurement entity disclaims any factual/ or other errors in the bidding document (the onus is purely on the individual bidders to verify such information) and the information provided therein are intended only to help the bidders to prepare a logical bid-proposal.
- 10. The provisions of RTPPA Act 2012 and Rules 2013 thereto shall be applicable for this procurement. Furthermore, in case of any inconsistency in any of the provisions of this bidding document with the RTPP Act 2012 and Rules thereto, the later shall prevail.

Process for Participation & Depositing Payment Online

JAIPUR DEVELOPMENT AUTHORITY, has decided to receive Bidding document fee, RISL Processing Fee and Bid Security Deposit (BSD) through online mode only for which the bidder has to get registered himself on JDA portal www.jda.urban.rajasthan.gov.in.

To participate in the bid, bidder has to be:

- 1. Registered on JDA website www.jda.urban.rajasthan.gov.in (by depositing Rs. 1000.00 online, the validity of which remains 3 (three) years).
 - For participating in the Bid, the Bidder has to apply for this Bid and pay the Bid Document Fee, RISL Processing Fee and Bid Security Deposit, online only.
- 2. Registered on e-Procurement Portal of Government of Rajasthan www.eproc.rajasthan.gov.in for online e-Bid submission.

Methods for depositing on line amount

Option-1: Bank Guarantee (BG) against EMD / Bid Security

Bidder may opt Bank Guarantee (BG) against EMD (Bid Security), for which bidder requires to prepare BG before applying in the tender. The details of BG requires to be fed on JDA portal before paying balance amount (Tender Fee + RISL Processing Fee). This amount will be paid through Payment Gateway only, option to make balance payment through EFT (RTGS/NEFT) will not be available.

If bidder does not opt for BG against EMD, options of making complete payment through Payment Gateway or through EFT (NEFT / RTGS) will be available.

Option-2: Electronic Fund Transfer (EFT: NEFT/RTGS)

If the bidder selects payment mode as EFT (NEFT/RTGS), "Paying Slip for EFT (NEFT/RTGS)" will be generated by the system for the complete amount. The payment can be made from any Bank any Branch using this Paying Slip through NEFT/RTGS (Claim against payment made through EFT in any other JDA bank account will not be acceptable and bidder stands disqualified from participation in the bid applied for). After successful transaction through NEFT/RTGS, as per the standard procedures it may take 4 to 24 hours in process of confirmation of EFT through Auto-Process depending on the time of EFT done. Therefore, option to make payment through EFT (NEFT/RTGS) will be available till 48 hours prior to closing date of bid participation.

Option-3: Payment Gateway (Aggregator)

The facility to make payment through Debit Card, Credit Card, Net banking etc., will be available. User can use this facility from anywhere any time till the closing date & time of bid participation.

C. Bid Participation Receipt

After confirming payment, the bidder will get Bid Participation Receipt on the basis of which user will get the payment details along with other details for bidding on e-Procurement portal of GOR.

- In case of BG as the remaining payment will be done through Payment Gateway, on successful transaction the "Bid Participation Receipt" will be generated on real time basis.
- In case complete payment is done through Payment Gateway, on successful transaction the "Bid Participation Receipt" will be generated on real time basis.

In case complete payment is done through EFT (NEFT/RTGS), on confirmation of payment from ICICI Bank (Auto Process) "Bid Participation Receipt" will be available on Login of Bidder on JDA portal.

Bidder has to submitted as proof of deposited amount against the Bid on eProcurement Portal

Jaipur Development Authority, Jaipur.					
Bid Participation Receipt					
	Date & Time:-				
Bid Detail					
Bid ID:	Procurement Entity:-				
Bid Title:					
Bid Value:	Bid Opening Place:				
Bidder Detail					
Name of Entity:	Mobile No.:				
Registration Type:	Instrument Amount:				
Payment Mode:	Payment Channel:				
Instrument No.:	Instrument Date:				

Dates Detail					
Sr. No.	Event Name	Event Date			
1	Publishing Date				
2	Bid Opening Date				

Specific Instrument for eProc Rajasthan					
Instrument Type					
Instrument Number	Head Name	Amount	Date		
Tender Fee					
RISL Processing Fee					
Bid Security Deposit					
Issuer Detail: Jaipur De	velopment Authority	Challan Number:			

Specified Bank Guarantee Performa

Section - 6

Form of (Bank Guarantee) -En cashable at branch of the bank in Jaipur City.

To,	
Secreta Jaipur Jaipur	Development Authority,
	Guarantee No dated for [amount of Security in figures] [in words] on behalf of [Name of the Bidder] against the Security Deposit for the work of "" (Name of
work).	`
Bidde	REAS, [name of Bidder with address] (hereinafter called "the r") has submitted his Bid datedfor the work of "".(Name of Work) (hereinafter called "the Bid").
	V ALL PEOPLE by these presents that we (Name of Bank) of having our registered office at [name of country] having our registered office at (hereinafter called "the Bank") are bound unto Secretary, Jaipur Development
Author Securi said Er	rity. (Hereinafter called "the Employer") in the sum of Rupees [Amount of ty in figures] (in words) only for which payment will and truly to be made to the mployer, the Bank binds itself, its successors, and assigns by these presents. In demand of JDA, this Bank Guarantee is encashable at following branch in Jaipur City.
1.	Name of Bank:
2.	Name of the branch with branch code:
3.	Address:
4.	E-Mail Id:
5.	Telephone No.
6.	Fax No.:
SEALI	ED with the Common Seal of the said Bank this day of of 20

THE CONDITIONS of this obligation are:

- (1) if the Bidder withdraws his Bid during the period of Bid validity specified in the Form of Bid;
- (2) if the Bidder refuses to accept the correction of errors in his bid;
- (3) If the Bidder, having been notified of the acceptance of his Bid by the Employer during the period of Bid validity;
 - (a) fails or refuses to execute the Form of Agreement in accordance with the Instructions to Bidders, or
 - (b) fails or refuses to furnish the Performance Security, in accordance with the Instructions to Bidders;

We undertake to pay to the Employer up to the above amount upon receipt of his first written demand, without the Employer having to substantiate his demand, provided that in his demand the Employer will note that the amount claimed by him is due to him owing to the occurrence of one or more of the above conditions, specifying the occurred condition or conditions.

This Guarantee will remain in force up to and including the date 30 days after the date of expiration of the Bid Validity, as stated in the Instructions to Bidders, or any such extension thereto as may be agreed by the Bidder, notice of which extension(s) to the Bank is hereby waived. Any demand in respect of this Guarantee should reach the Bank not later than the above date.

The amount covered under the above Bank Guarantee shall be automatically be credited in the accounts of JDA in ICICI Bank, JDA Campus, Jaipur through **ISFC code No ICICI0006754. Bank Account No. 675401700586** on the date of expiry or its validity, unless the agencies get it re-validated well before its expiry date or produce NOC from JDA in written for its release.

Date	Signature of the Bank	_
Witness	Seal	
[Signature, Name and Address]		

[Note: To be furnished on appropriate non-judicial stamps.]

JAIPUR DEVELOPMENT AUTHORITY, JAIPUR

SCHEDULE AND SPECIFICATIONS

NAME OF WORK: Miscellaneous Civil Work at Rajasthan International Centre, Jhalana, Jaipur

1. NIB No. : NIB No-02/2020-21 Dated 10.07.2020

2. Approximate cost : Rs. 235.68 Lacs

3. Cost of the bid document(Online) : Rs.1000/- The Bidders are required to submit Bid

security, cost of Bid documents, Bid processing fees through online payment after registering with JDA on www.jaipurjda.org/e-services/e-tenderportal. There should be a gap 3 working days between End date for Bid Applying, Online payment & Bid Submission and Bid Opening date. In the absence of such fees the bid of respective bidder will be considered as non-responsive

and shall be rejected.

4. Bid Processing Fees (Online) : Rs. 1000/-(In favour of M.D. R.I.S.L, Jaipur)

5. Earnest Money (In favour of Secretary, JDA, Jaipur) (Online)

@ 2% Rs. 4,71,352.00/-/-(For A&AA class contractor

registered in other department) and

@ 0.5% Rs. 1,17,838.00/-(For Contractor registered in JDA) through online payment after registering with JDA on www.jaipurjda.org/e-services/e-tenderportal. There should be a gap 3 working days between End date for Bid Applying, Online payment & Bid Submission and

Bid Opening date

6. Sale of Bid document Online : 10.07.2020 from 10.00 AM to 11.08.2020 upto 6.00 PM

7. Date & Time of receiving tender

Online

11.

8. Dates & Place for Physical BG 13.08.2020 from 10.00 AM to 13.08.2020 upto 5.00 PM

Submission

Place: Office of D.D. (E&B), Room No. MB-SF-225A, Main

10.07.2020 from 10.00 AM to 11.08.2020 upto 6.00 PM

Building, Jaipur Development Authority, JLN Marg, Jaipur

9. Date of Submission of Bid : 11.08.2020 upto 6.00 PM through online payment after

registering with JDA on www.jaipurjda.org/e-services/e-tenderportal. There should be a gap 3 working days between End date for Bid Applying, Online payment &

Bid Submission and Bid Opening date.

10. Date of opening of tender : 14.08.2020 at 11.00 AM in MB-FF-106, First Floor,

Main Block, Ram Kishore Vyas Bhavan, Indira Circle, Jawahar Lal Nehru Marg, Jaipur – 302004 (Rajasthan)

Completion period of work : 12 Months

SCHEDULE – A: INFORMATION USEFUL FOR THE CONTRACTORS:

The Tenderer should see the site and fully understand the conditions of the site before tendering and include all leads, lift etc for the material in his item rate/percentage to be quoted on the rates give in the Schedule 'G'. The work shall be carried out in accordance with the MORTH/Rajasthan PWD detailed specification and to the entire satisfaction of the Engineer – In – Charge of the work.

SCHEDULE – B: LIST OF THE DRAWING TO BE SUPPLIED BY THE DEPARTMENT:

The drawing may be seen in office of the undersigned.

<u>SCHEDULE – C: LIST OF THE DRAWING TO BE SUPPLIED BY THE CONTRACTOR:</u> List of the drawing to be supplied by the contractor NIL. But the contractor shall have to arrange at his own cost drawings required for the work after deposition necessary cost with JDA.

SCHEDULE - D: TEST OF THE MATERIALS:

The test of the materials and workmanship shall be conducted by the JDA staff as necessary. The result of such tests should confirm to the standard laid down in the Indian standard MORTH/PWD detailed specification. Qualified personnel as required under the contractor enlistment rules duly approved by the Deptt. Shall have to be engaged at site by the Contractor. The deptt. Reserves the right to engage such staff and recover the expenses from the contractor on such account in case of his failure to do so.

<u>SCHEDULE – E: SAMPLES OF THE MATERIALS:</u>

The sample of the materials to be used by the contractor shall be deposited 15 days In advance with the Engineer In charge and be got approval by him before use.

SCHEDULE - F: TIME OF COMPLETION:

The work should start within 10 days of issue of work order and complete within time limits.

SCHEDULE - G: ATTACHED SEPARATELY

SCHEDULE – H: SPECIAL CONDITION: Attached Separately.

SCHEDULE 'I': LIST OF MATERIAL TO BE SUPPLIED BY THE DEPARTMENT:

Cement if available in JDA store shall be issued @ the prevailing stores issue rate of JDA + 5% storage charges at the time of issue of cement.

Material if available time JDA store shall be issued @ the prevailing stores rate of JDA + 5% storage charges. Annexure-3: Special Provision of the work plan- Qualification criteria and methodology of roads category - I&II.

SCHEDULE 'J': COST OF BID DOCUMENTS, PROCESSING FEES & EARNEST MONEY.

- 1. Date of submission of Bid Cost, Process Cost & EMD upto **11.08.2020** upto 6.00 PM through online payment after registering with JDA on www.jda.urban.rajasthan.gov.in/e-services/e-tender portal. There should be a gap 3 working days between End date for Bid applying, Online payment & Bid submission and Bid Opening date. In the absence of such fees the bid of respective bidder will be considered as non-responsive and shall be rejected.
- 2. A bidder can submitted bid security deposit through bank guarantee, if a bidder opt bid security to be deposited through Bank guarantee, the bank guarantee should be valid for next **Twelve** month after the bid opening date. A copy of the such bank guarantee will be required to be attached with the bid submission document uploaded on E-procurement portal of GOR. The bank guarantee will be physically handed over upto prescribed time to Nodal officer of on-line tendering system on JDA i.e. D.D.(E&B) in room No. NB-SF- 215E of Extension Building, Jaipur Development Authority, Jaipur, as per specified in bid documents, Annexuer-5. Bank Guarantee Will be in specified performa enclosed with this bid documents.

EXECUTIVE ENGINEER (PROJECT-II) JDA, JAIPUR.

SPECIAL CONDITIONS

SCHEDULE 'H'

- 01. Use of Bitumen mixture Tar mechanical lime grinder, cement concrete mixer & vibrator is essential for the work. This shall have to be arranged by the contractor at his own level/cost.
- 02. If there is any typographical error or otherwise in the 'G' Schedule the rates given in the relevant BSR on which Schedule 'G' has been prepared, shall prevail.
- 03. The contractor shall follow the contractor lab our regulation and abolition Act 1970 & Rule 1971.
- 04. The JDA shall have right to cause an audit and technical examination of the work and the final bills of the contractor including all supporting vouchers, abstract etc. to be made within two years after payment of the final bills and if as a result such audit any amount is found to have been over paid/excess in respect of any work done by the contractor under the contract or any work claimed by him to have been done under this contract and found not to have been executed the contractor shall be liable to refund such amount and it shall be lawful ;for the JDA to recover such sum from him in the manner prescribed in special condition no. 8 or any other manner legally permissible and if it is found that the contractor was paid less then that was due to him under the contract in respect of any work executed by him under it, the amount of such under payment shall be paid by the JDA to the contractor.
- 05. The contractor shall not work after the sunset and before sunrise without specific permission of the authority Engineer.
- 06. Whenever any claim against the contract for the payment of a sum of money arises out of under the contracts, the JDA shall be entitled to recover the sum by appropriating in part or whole of the security deposit of the contractor. In the event of the security being insufficient or if no security has been taken from the contractor then the balance of the total sum recoverable as the case may shall be deducted from any sum then due or which at any time there contract with the JDA should this sum be sufficient to recover the full amount recoverable. The contractor shall pay to JDA on demand the balance remaining due. The JDA shall further have the right to affect such recoveries under P.D.R. Act.
- 07. The rate quoted by the contractor shall remain valid for a period of 4(four) months from the date of opening of the tenders.
- 08. By submission of this tender the contractor agree to abide with all printed conditions provided in the PWD manual form 64 (Chapter 3 para 36) and subsequent modification.
- 09. No conditions are to be added by the contractor and conditional tender is liable to be rejected.
- 10. All transaction in the execution of this work and this tender will be liable to sale-tax vide section 2(B) read with sub clause (4) Sale-tax Rule, 1954.
- 11. If any tenderer withdraws his tender prior to expiry of said validity period given at S. No. 7 or mutually extended prior or makes modifications in the rates, terms and conditions of the tender within the said period, which are not acceptable to the department or fails to commence the work in the specified period, fails to execute the agreement and fails to furnish performance guarantee the department shall without prejudice to any, other right or remedy, be at liberty to forfeit the amount of earnest money given in any form absolutely. If any contractor, who having submitted a tender does not execute the agreement or start the work or does not complete the work and the work has to be put to retendering, he will stand debarred from participating in tendering in JDA for Six Months in addition to forfeiture of Earnest Money/Security Deposit/Performance Guarantee and other action under agreement.
- 12. The contractor shall arrange his own machinery required for the work such as Bitumen Mixer, Hot Mix plants and paver road roller, Tar boiler, sprayer etc.
- 13. The contractor shall arrange his own storage tanks up to 10 Tonnes capacity for storing bulk bitumen wherever

- supplied by the department.
- 14. Rules regarding enlistment of contractors provide that work up to the time five times limit for which they are qualified for tendering can be allotted to them Therefore, before tender the contractors will keep this in mind, and submit the details of work. Tenders with incomplete or incorrect information are liable to be rejected.
- 15. Any material not conforming to the specifications collected at site shall have to be removed by the contractor within a period of 3 days of the instructions, issued by the Engineer-In-charge in writing failing which, such material shall be removed by the Engineer-In charge at risk and cost of the contractor after expiry of 3 days period.
- 16. The material collected at site and paid provisionally shall remain under and ward of the contractor till it is consumed, fully on the work.
- 17. The rates provided in tender documents are inclusive of all Taxes/royalty.
- 18. For paver work at least 3 road rollers shall be simultaneously deployed.
- 19. Bitumen for tack coat or any other purposes shall be applied only by a bitumen sprayer of a mechanical pressure.
- 20. No extra lead of earth/material shall be paid over and above as specified in 'G' schedule. Source/borrow pit area for earth shall have to be arranged by the Contractor at his own cost.
- 21. Undersigned has full right to reject any or all tenders without given any reasons.
- 22. Mortar of Masonry work and lean concrete will be permitted mixer with hopper.
- 23. As per Supreme Court decision "All contracts with Governments shall require registration of workers under the building and other construction workers (Regulation of Employment and Conditions of Service) Act, 1996 and extension of benefits to such workers under the act."
- 24. Special Conditions of Contract regarding Defect Liability Period (DLP) for various works costing Rs. 25.00 lacs and more shall be applicable
- 25. The tenderer are required to submit copy of their enlistment as contractor.
- 26. Conditions of RPWA-100 will be mandatory & acceptable to the contractor.
- 27. Any tender received with unattested cutting/overwriting in rates shall be rejected and such bidder will be debarred from tendering for three months in JDA.
- 28. The contractor will have to install display boards at site of work as directed by Engineer in charge. Failing which penalty of Rs. 5000.00 per day will be imposed.
- 29. All the provisions of THE RAJASTHAN TRANPARENCY IN PUBLIC PROCUREMENT ACT, 2012 and Rules, 2013 will be applicable. If there is any contradiction in existing special conditions and provisions of THE RAJASTHAN TRANPARENCY IN PUBLIC PROCUREMENT ACT, 2012 and Rules, 2013 provisions of THE RAJASTHAN TRANPARENCY IN PUBLIC PROCUREMENT ACT, 2012 and Rules, 2013 shall be applicable.

EXECUTIVE ENGINEER (PROJECT-II) JDA, JAIPUR.

Signature of the Contractor With full Address, Mob No, Landline No & E-mail address

Special Conditions of Contract regarding Defect Liability Period (DLP) for Various works costing Rs. 25.00 Lacs and more

(a) The routine maintenance activities and their periodicity as per JDA Office order no: JDA/Ex.En.(TA to Dir Engg.-I)/2016/D-29 dated 11.03.2016

Table-I

S.No.	Type of work	DLP Period
1	Bridge work	5 Years
2	CD work	5 Years
3	CC road, PQC work	5 Years
4	CC tiles/Kerb/ Medians	5 Years
5	Drains	3 Years
6	Roads	
	(i) Two Layer WBM/GSB	6 Months or one full rainy season whichever is later
	(ii) For Renewal/Strengthening	
	(a) BT upto 30 mm thickness	1 Year
	(b) BT above 30 mm to upto 40 mm	2 Years
	(c) BT above 40 mm to upto 90 mm	3 Years
	(d) BT above 90 mm	5 Years
	(iii) New roads	
	(a) BT upto 90 mm	3 Years
	(b) BT more than 90 mm	5 Years
7	Compound wall	3 Years
8	Building work	
	(i) Work pertaining to sanitary works electrical works, Joinery	2 Years
	works and painting works.	
	(ii) Work pertaining to building structure and other civil works.	5 Years
9	Electric work except maintenance	3 Years
10	Sewer/water supply all including STP and water supply related work except maintenance works	3 Years

1. DRAINAGE WORKS

- 1.1 The Defect Liability Period (DLP) for all Drainage works including all related work shall be Three years. Drainage works executed by the Contracting agency shall be maintained by them at their own cost for three years (DLP) from the actual date of completion of work as per the clause in the Contract Agreement and Special Condition of Contract.
- 1.2 No extra payment shall be made to the contracting agency on account of maintenance of Drain works and removal of defect during Defect Liability Period.
- 1.3 The word "Drainage Works" means all new Drain Works construction, its covering work, cleaning inside and other works."
- 1.4 The word "Maintenance of Drain Works during Defect Liability Period" means
 - (i) Routine maintenance of Drain Works including cleaning the drains, spouts etc and carriage of malba etc from the site.
 - (ii) To remove the defect as & when appear in part and entire structure of Drain Works, in specified time and keeping the Drain clean & good condition. and
 - (iii) Damages due to improper drainage / drains, local flooding, depressions on roads etc.
- 1.5 The contracting agency shall do the routine maintenance of Drain works, including pavement, road side and

cross drains including surface drains to the required standards and keep the entire Drain surface and structure in Defect free conditions during the entire period of routine maintenance, which begins at completion of the construction work and ends after three years.

- 1.6 The routine maintenance shall consist of the routine maintenance operation defined in manual for maintenance of roads of MoRTH and shall be carried out accordingly.
- 1.7 The Drain maintenance activities and their periodicity

S.N	Name of Item/Activity	Frequency of operations in one year
О.		
1	Restoration and cleaning of rain water spouts & repair of	Once in a year, generally before rains.
	any type of damages.	
2	Cleaning of inner portion of the drains by removing the	As and when required.
	covers at regular interval and carriage and disposal of	
	malba etc.	
3	Insurance of proper functioning of drains including civil	As and when required.
	maintenance and desilting of drains.	

2. General

- 2.1 Inspection of works during Defect Liability Period
- 2.1.1 The contracting agency shall undertake joint detailed inspection along with Engineer-in-charge/A.En., at IDP once in three months in case of all Drain works. The Engineer-in-charge can reduce this frequency in case of emergency. The Contracting agency shall forward to the Engineer-in-charge the record of inspection and rectification immediately after the joint inspection. The Contracting agency shall pay particulars attention on those Drain sections, which are likely to be damaged during rainy season.
- 2.1.2 One register has to be maintained by every A.E.n for recording the inspection details of works in his jurisdiction under defect liability period.
- 2.2 Conditions regarding Security Deposit
- 2.2.1 Security for DLP-

The contracting agency shall have to furnish security deposit (SD) in the form of Bank Guarantee valid from the actual date of completion, which shall be assigned by the Engineer-in-charge.

2.2.2 Refund of SD –

The release of SD amount shall be as following table:-

S.No.	Released SD	1 st year	2 nd year	3 rd year	5 th year
	DLP period				
1	Upto 1 year	100 %	40 %	20 %	10 %
2	Upto 2 Year		60 %	20 %	10 %
3	Upto 3 Year			60 %	10 %
4	Upto 4 Year				20 %
5	Upto 5 Year				50 %

Various conditions for managing DLP are as under:-

(i) At the time of completion of work, final component shall be worked out for each individual item like

- BT/CC /tiles/drains etc (as per different categories in Table I), DLP shall be operative based upon type of individual item ex:- CC-5 years, BT- 1/2/3/5 years, Drain- 3 years etc.
- (ii) Similarly for all new works, these components should be calculated at the time of TS itself, which should be made part of BID document.
- (iii) If any work, amount is less than Rs. 25 lakhs but later on due to extra/excess work, if amount of final work crosses more than Rs. 25 lakhs, DLP shall be operative as per rule for each individual item.
- (iv) Similarly if any work is more than Rs. 25 lakhs but later finalization amount of work is less than Rs. 25 lakhs, DLP should be operative for six months or rainy season whichever is late.
- (v) During DLP period if contractor fails to repair any work even after issue of 7 days written notice, same work shall be got executed by respective Executive Engineer at the contractor's risk and cost. This process shall be applicable throughout the DLP period. After completion of DLP period in such works contractor should be debarred and blacklisted from JDA for three years as per RTPP Rule 2012 and 2013 where he defaults twice in a single agreement or in two different works.
- (vi) Quarterly inspection as per rules shall be carried out and DLP registers shall be maintained by respective Executive Engineers to monitor the DLP repairs.
- (vii) Special and regular inspection shall also be carried out as per order no. JDA/Ex.En & TA to DE-I/ 2014-15/D-223 dated 12.03.2015 and order no. SE (PMGSY) CIRCULAR 2006/D-115 dated 04.05.2006 point no. 3
- (viii) In case JDA feels to take up work on any existing DLP road due to any reason, following procedure should be adopted.
 - (a) At the time of withdrawal total liability of repairs as per DLP conditions to be carried out and contractor shall be asked to complete the same. After completion of assessed repairs DLP period shall be released after deduction amt. as per table III.

% recovery on withdrawal of DLP of work order DLP period	1 Year	2 Year	3 Year	4 Year	5 Year
1 Year	1.12	-	-	-	-
2 Year	2.55	1.43	-	-	-
3 Year	4.38	3.26	1.83	-	-
5 Year	9.00	7.88	6.45	4.62	2.47

Note:- Calculation is to be done on quarterly basis.

- (b) In case Contractor fails to carry out these repairs, same shall be carried out at his risk and cost. If the total amt. of such repairs works out to be more than total retained amt. of SD, same shall be recovered from other works and as per PDR rules. The amount as per Table-III is also to be deducted in addition to this amount.
- (ix). Based upon type of work, DLP conditions for works to be carried out during DLP period with their frequency of respective type of work shall be prepared by respective SE's after approval of these periods.

2.2.3 Force Majeure

The defect arises due to earthquake, cyclone, and natural calamities shall not be the responsibly of contracting agency.

Signature of Contractor With Full Address Executive Engineer (Project-II)
JDA, Jaipur.

Annexure A: Compliance with the code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall:-

- (a) Not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process.
- (b) Not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation.
- (c) Not indulge in any collusion, Bid rigging or anti- competitive behavior to impair the transparency, fairness and progress of the procurement process.
- (d) Not misuse any information shared between the procuring entity and the bidders with intent to gain unfair advantage in the procurement process.
- (e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process.
- (f) Not obstruct any investigation or audit of a procurement process.
- (g) Disclose conflict of interest, if any and.
- (h) Disclose any previous transaction with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of Interest:-

The Bidder participating in bidding process must not have a Conflict of Interest.

A Conflict of Interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- i. A Bidder may be considered to be in conflict of interest with one or more parties in a bidding process of, including but not limited to:
 - a. Have controlling partners/ shareholders in common, or
 - b. Receive or have received any direct or indirect subsidy from any of them, or
 - c. Have the same legal representative for purposes of the Bid, or
 - d. have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the bid of another Bidder, or influence the decisions of the procuring entity regarding the bidding process. Or
 - e. The Bidder participates in more than one Bid in a bidding process. Participation by a Bidder in more than one bid will result in the disqualification of all bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a Bidder, in more than one bid, or.
 - f. The Bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the Goods, works or services that are the subject of the Bid.
 - g. Bidder or any of its affiliates has been hired (or is proposed to be hired) by the procuring entity as engineer in charge/ Consultant for the contract.

Annexure B: Declaration by the Bidder regarding Qualifications:-

Declaration by the Bidder

In	relation	to	my/	our	Bid	submitte	d to)	for
procu	arement of]	In	response to their Notice Inviting Bids
No.		Date	d			I/We	hereb	у	declare under section 7 of Rajasthan
Trans	sparency in	Pub	lic Pro	ocure	ment A	Act. 2012	that:		
1. I/w	e possess t	he ne	ecessa	ry pr	ofessi	onal, tech	nical,	, fi	inancial and managerial resources and
cor	mpetence re	equire	ed by	the B	idding	g Docume	nt iss	ue	ed by the Procuring Entity:
2. I/ v	we have ful	filled	l my/c	our ob	ligati	on to pay	such (of	the taxes payable to the union and the
Sta	ite Governr	nent	or any	loca	l auth	ority as sp	ecifie	ed	in the Bidding Document.
3. I/w	e are not	insol	vent,	in re	ceivei	ship, ban	krupt	0	or being wound up, not have my/our
aff	airs admini	istere	d by	a cou	ırt or	a judicial	offic	cer	, not have my/our business activities
sus	spended and	d not	the su	ıbject	of leg	gal procee	ding f	foi	r any of the foregoing reasons:
4. I/w	e do not h	ave,	and o	ur dir	ectors	and offic	ers n	ot	have, been convicted of any criminal
off	ence relate	ed to	my/o	our p	rofess	ional cor	duct	O1	r the making of false statements or
mis	srepresenta	tions	as to	my/c	ur qu	alificatior	s to e	ent	ter into a procurement contract within
a p	period of th	ree y	ears p	preced	ding t	he comme	encem	ner	nt of this procurement process, or not
hav	ve been oth	erwis	se disc	qualif	ied pu	rsuant to	debar	m	ent proceedings;
5. I/w	e do not l	nave	a cor	ıflict	of int	erest as	specif	ie	d in the Act, Rules and the Bidding
Do	cument, wl	hich 1	materi	ially a	ffects	fair comp	etitic	on;	;
Date:	:						Si	gn	nature of bidder
Place	:						Na	an	ne:
							D)es	signation:
							A	dc	dress:

Annexure C: Grievance Redressal during Procurement Process

The designation and address of the first Appellate Authority is **JDC**

The designation and address of the Second Appellate Authority is **E.C.**

(1) Filling an appeal:

If any Bidder or prospective bidder is aggrieved that any decision, action or omission of the Procuring Entity is in contravention to the provisions of the Act or the Rules or the Guidelines issued there under, he may file an appeal to First Appellate Authority, as specified in the Bidding Document with in a period of ten days from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or grounds on which he feels aggrieved:

Provided that after the declaration of a Bidder as successful the appeal may be filed only by a Bidder who has participated in procurement proceedings:

Provided further that in case a Procuring Entity evaluates the Technical Bids before the opening of the Financial Bids, an appeal related to the matter of financial Bids may be filed only by a Bidder whose Technical Bid is found to be acceptable.

- (2) The officer to whom an appeal is filed under Para (1) shall deal with the appeal as expeditiously as possible and shall endeavor to dispose it of within thirty days from the date of the appeal.
- (3) If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the Bidder or prospective bidder or the Procuring Entity is aggrieved by the order passed by the First Appellate Authority, the Bidder or Prospective bidder or the Procuring Entity, as the case may be, may file a second appeal to second Appellate Authority specified in the Bidding Document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the first Appellate Authority, as the case may be.

(4) Appeal not to lie in certain cases.

No appeal shall lie against any decision of the Procuring Entity relating to the following matters, namely:-

- (a) Determination of need of Procurement;
- (b) Provisions limiting participation of bidders in the Bid process;
- (c) The decision of whether or not to enter into negotiations;

- (d) Cancellation of a procurement process;
- (e) Applicability of the provisions of confidentiality;

(5) Form of Appeal:

- (a) An appeal under Para (1) or (3) above shall be in the annexed form along with as many copies as there are respondents in the appeal.
- (b) Every appeal shall be accompanied by an order appealed against, if any affidavit verifying the facts stated in the appeal and proof of payment of fee.
- (c) Every appeal may be presented to First Appellate Authority or Second Appellate Authority, as the case may be in person or through registered post or authorized representative.

(6) Fee for filing appeal:

- (a) Fee for first appeal shall be rupees two thousand five hundred and for second appeal shall be rupees ten thousand, which shall be non- refundable.
- (b) The fee shall be paid in the form of Bank demand draft or banker's cheque of a Scheduled Bank in India payable in the name of Appellate Authority concerned.

(7) Procedure for disposal of appeal:

- (a) The first Appellate Authority or Second Appellate Authority, as the case may be upon filing of appeal, shall issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing.
- (b) On the date fixed for hearing, the First Appellate Authority or Second Appellate Authority, as the case may be shall,
 - (i) Hear all the parties to appeal present before him and
 - (ii) Peruse or inspect documents, relevant records or copies there or relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the Appellate Authority concerned shall pass an order in writing and provide the copy of order to the parties to appeal free of cost.
- (d) The order passed under sub-clause (c) above shall also be placed on the state public Procurement Portal.

Annexure D: Additional Conditions of Contract

1. Correction of arithmetical errors

Provided that a financial Bid is substantially responsive, the procuring entity will correct arithmetical errors during evaluation of Financial Bids on the following basis:

- i If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected, unless in the opinion of the procuring Entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted shall govern and the unit price shall be corrected;
- ii If there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail and the total shall be corrected; and
- iii If there is a discrepancy between words and figures, the amount in words shall prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures shall prevail subject to (i) and(ii) above

If the Bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid shall be disqualified and its Bid Security shall be forfeited or its Bid Securing Declaration shall be executed.

2. Procuring Entity's Right to Vary Quantities:

- (i) At the time of award of contract, the quantity of Goods, works or services originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed twenty percent, of the quantity specified in the Bidding Document. It shall be without any change in the unit prices or other terms and conditions of the Bid and the conditions of contract.
- (ii) If the Procuring Entity does not procure any subject matter of procurement or procures less than the quantity specified in the Bidding Document due to change in circumstances, the bidder shall not be entitled for any claim or compensation

except otherwise provided in the conditions of contract.

(iii) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity shall not be more than 25 % of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the Supplier fails to do so, the Procuring Entity shall be free to arrange for the balance supply by limited Bidding or other wise and the extra cost incurred shall be recovered from the supplier.

3. <u>Dividing quantities among more than one Bidder at the time of award (In case of Procurement of Goods)</u>

As a general rule all the quantities of the subject matter of procurement shall be procured from the Bidder, whose Bid is accepted. However, when it is considered that the quantity of the subject matter of procurement to be procured is very large and it may not be in the capacity of the Bidder, whose bid is accepted, to deliver the entire quantity or when it is considered that the subject matter of procurement to be procured is of critical and vital nature, in such cases, the quantity may be divided between the Bidder, whose Bid is accepted and the second lowest Bidder or even more bidders in that order, in a fair, transparent and equitable manner at the rates of the Bidder, whose Bid is accepted.

[See rule 83]

Memorandum of Appeal under the Rajasthan Transparency in Public Procurement Act, 2012

Appe	al No Ot
	Before the (First
Seco	nd Appellate Authority)
1.	Particulars of appellant :
	(i) Name of the appellant:
	(ii) Official address, if any:
	(iii) Residential address:
2.	Name and address of the respondent (s):
	(i)
	(ii)
	(iii)
3.	Number and date of the order appealed against and name and designation of the
	officer/authority who passed the order (enclose copy), or a statement of a
	decision, action or omission of the Procuring Entity in contravention to the
	provisions of the Act by which the appellant is aggrieved:
4.	If the Appellant proposes to be represented by a representative, the name and
	postal address of the representative:
5.	Number of affidavits and documents enclosed with the appeal:
6.	Grounds of appeal:
	(Supported by an affidavit)
7.	Prayer
Place	
Date	

Appellant's Signature

JAIPUR DEVELOPMENT AUTHORITY, JAIPUR

"G"- SCHEDULE

BSR For : 2016 JDA BSR (Building Works)-2015-2016 2016 JDA BSR (Road Works)-2015-2016 2016 JDA BSR (Sanitary Works)-2015-2016

Name of Work: Miscellaneous Civil Work at Rajasthan International Centre, Jhalana, Jaipur.

S.No.	Item Description	Quantity	Rate (Rs.)	Unit	Amount (Rs.)
012101	Earth work in excavation by mechanical means (Hydraulic Excavator)/	~ ,	,		,
	manual means in foundation trenches or drains (not exceeding 1.5 m in				
	width or 10 sum on plan) including dressing of sides and ramming of				
1	bottoms, lift upto 1.5 m, including taking out the excavated soil and				
	depositing and refilling of jhiri with watering & ramming and disposal of				
	surplus excavated soil as directed with in a lead of 50 meter. All kinds of				
	soils	1978.200	111.60	cum	220767.12
•	Add extra for foundation/trenches/drains for every additional lift of 1.5				
2	Mtr. or part thereof in				
	All kinds of soil				
	Add Extra for lift above 1.5 mtr to 3 mtr	750.000	21.60	cum	16200.00
	CEMENT CONCRETE (CAST-IN-SITU)				
	Providing and laying in position cement concrete including curing,				
3	compaction etc. complete in specified grade excluding the cost of centering				
	and shuttering - All work up to plinth level.				
	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal				
	size).	365.760	2058.30	cum	752843.81
	DAMP- PROOF COURSE AND PRECASTCOPING				
	Providing and laying damp-proof course with cement concrete grade M-				
4	150 (1:2:4) mortar prepared with 1% solution of water-proof compound				
	complete as per specification .				
	50mm thick.	174.934	243.90	sqm	42666.40
	CAST-IN-SITU CONCRETE				
	Providing and laying in position specified grade of cement concrete for all				
	RCC structural elements upto plinth level including curing, compaction,				
	finishing with rendering in cement sand mortar 1:3 (1 cement: 3 coarse				
5	sand) and making good the joints and cost of plastizers(if required)				
	excluding the cost of centering, shuttering and reinforcement.				
	M20 grade Nominal Mix / Design Mix				
	, 0	14.400	2961.00	cum	42638.40
	Providing and laying in position specified grade of cement concrete for				
	RCC structural elements upto floor five level including curing,				
	compaction, finishing with rendering in cement sand mortar 1:3 (1 cement:				
	3 coarse sand) and making good the joints and cost of plastizers (if				
6	required) excluding the cost of centering, shuttering and reinforcement for				
	Walls (any thickness) including attached pilasters, buttresses, plinth and				
	string courses, fillets, columns, pillars, piers, abutments, posts and struts				
	etc.				
	M20 orade Nominal Mix / Design Mix	15.660	3673.80	cum	57531.71
	Providing and laying in position specified grade of cement concrete for				
	RCC structural elements upto floor five level including curing,				
	compaction, finishing with rendering in cement sand mortar 1:3 (1 cement:				
	3 coarse sand) and making good the joints and cost of plastizers(if				
7	required) excluding the cost of centering, shuttering and reinforcement for				
	Beams, suspended floors, roofs, griders having slopes up to 15°, landings,				
	balconies, shelves, chajjas, lintels, bands, plain windows sills, staircases				
	and spiral staircases etc.	405			
	M20 orade Nominal Mix / Design Mix	102.090	3232.80	cum	330036.55
	Add extra for providing richer mixes respectively at all floor levels				
8	Providing M-25 grade concrete by using min 410 kg of cement per cum	404	F4.33		(T1=00
-	instead of M-20 grade design mix.	131.528	51.30	cum	6747.39

	Providing and laying in nocition anneitied are do of someth commute for				
	Providing and laying in position specified grade of cement concrete for				
	RCC structural elements upto floor five level including curing, compaction, finishing with rendering in cement sand mortar 1:3 (1 cement:				
	3 coarse sand) and making good the joints and cost of plastizers(if				
	required) excluding the cost of centering, shuttering and reinforcement for				
9	Arches, arch ribs, domes, vaults, shells, folded plate, chimneys, shafts,				
	roofs having slope more than 15°, vertical and horizontal fins individually				
	or forming box louvers, facias and eaves boards				
	M20 grade Nominal Mix / Design Mix				
	11120 Grade Norman 11111/ Design 11111	77.203	3466.80	cum	267647.36
	FORMK WORK				
	Centering and Shuttering with plywood or steel sheets including strutting,				
10	propping bracing both ways and removal of formwork for foundation,				
	footings, strap beam, raft, bases of columns etc.	157.136	99.00	sqm	15556.46
	Centering & shuttering with plywood or steel sheets including strutting,				
11	propping bracing both ways with steel props and removal of formwork				
	for upto floor five level for: Walls (any thickness) including attached piloeters buttresses				
11.1	Walls (any thickness) including attached pilasters, buttresses	1418.260	180.90	eam	256563,23
	plinth and string course. Suspended floors, roofs, landings, staircases, balconies, girders,	1410.200	100.90	sqm	230303,23
11.2	cantilevers, bands, coping bed plates, anchor blocks, sills, chhajjas, lintel,				
11,2	beam, plinth beam etc.	575.214	212.40	sqm	122175.45
11.3	Columns, pillars, posts and struts etc.	44.280	234.00	sqm	10361.52
	Add 20% extra for shuttering in circular work (in respective centering and		2 = . 0 0		
11.4	shuttering items)	1342.660	0.00	sqm	0.00
	Add extra for additional height in centring, shuttering where ever			•	
	required with adequate bracing, propping etc. including cost of de-				
12	shuttering and decentring at all levels, over a height of 3.5 m, for every				
	additional height of 1 metre or part thereof (Plan are is to be measured)				
	•	540.000	107.10	sqm	57834.00
	STEEL REINFORCEMENT				
	Providing and fabricating reinforcement for R.C.C. work including				
13	straightening, cutting, bending, placing in position and binding (including				
	cost of binding wire) all complete up to floor five level.	14000 500	(2.10	1	000047.05
	Thermo-mechanically Treated bars (Conforming of relevent IS code)	14208.500	62.10	kg.	882347.85
14	Brick work with F.P.S. bricks of class designation 75 in superstructure				
14	above plinth level upto floor V level in all shapes and sizes in :				
	Cement mortar 1 : 6 (1 cement : 6 coarse sand)	294.005	2949.30	cum	867108.95
	Stone work (machine cut edges) for Wall cladding/ Veneering work up to		_, _,,,,,,	24111	221 200.70
	10m height with 20 to 30 mm thick Red Sand Stone (Karauli) and backing				
	filled with a grout of 12mm thick cement mortar 1:3 (1 cement : 3 coarse				
15	sand) including pointing in white cement mortar 1:2 (1 white cement : 2				
	stone dust) with an admixture of pigment matching the stone shade : (To				
	be secured to the backing by means of cramps which shall be paid				
	separately)				
	Exposed face machine cut	1517.036	1558.80	sqm	2364755.72
	Providing and fixing stainless steel cramps of required size and shape for				
	anchoring stone wall lining to the backing or securing adjacent stones in				
16	stone wall lining in cement mortar 1:2 (1 cement : 2 coarse sand) including				
	making the necessary chases in stone and holes in walls wherever required	2000 000	400.70	1	2017000 00
	Cumplying and fiving machine aut fine duesced D-1/Dinternal at 1	8000.000	489.60	kg.	3916800.00
	Supplying and fixing machine cut fine dressed Red/Pink sand stone dasa				
17	or coping, with full moulding if required laid on cement mortar 1:4				
	including pointing with admixture of pigment matching with the stone shade.				
	50 mm thick	532.286	909.00	sqm	483847.97
	Random Rubble stone masonry for with hard stone in foundation and	552.200	, , , , , ,	34111	100011.01
18	plinth in Cement Sand mortar above 30 CM thick wall in:				
	Cement Mortar 1:6 (1-Cement : 6-Sand).	124.950	1770.30	cum	221198.99
	Providing and fixing Granite stone slab mirror polished and machine edge				
	cut in walls, pillars, steps, Shelves, Sills Counters, Floors etc. laid on 12mm				
	(Av.) thick base of cement mortar 1:3 (1 cement : 3 coarse sand) jointing				
19	with white cement mortar 1:2 (1white cement : 2 marble dust) with				
	pigment to match the shade of the marble slab including grinding, rubbing				
	and polishing complete.				
	T				
	Jhunjhunu / Jalore (Red / Choclate Colour)	E04.51:	0.100.15		4.0000000
	Above 3601 Cm2 Slabs	594.316	2402.10	sqm	1427606.46

		1		ı	
	Extra in marble flooring work for upto 50 mm wide strip of Green/White/				
20	Jaisalmer stone in flooring work as per direction of Engineer in Charge				
		1600.000	34.20	R.Mtr.	54720.00
	Extra for providing edge moulding to 15-18mm thick marble/ Granite				
	stone counters, Vanities etc. including machine polishing to edge to give				
21	high gloss finish etc. complete as per design approved by Engineer-in-				
	Charge. Granite Work	721 400	152.00		110274.20
		721.400	153.00	mtr.	110374.20
	Providing and fixing pressed steel door frames confirming to IS 4351				
	manufactured from commercial mild steel sheet of 1.25 mm thickness				
	including hinges jamb, lock jamb, bead and if required angle threshold of				
	mild steel angle of section 50x25mm, or base ties of 1.25mm pressed mild				
22	steel welded or rigidly fixed together by mechanical means, adjustable				
	lugs with split end tail to each jamb including steel butt hinges 2.5mm				
	thick with mortar guards, lock strike-plate and shock absorbers as				
	specified and applying a coat of approved steel primer after pre-treatment				
	of the surface including filling with CC 1:2:4(M15 grade) complete as				
	directed by Engineer-in-charge:				
	directed by Engineer-in-charge.				
	Profile E	96.000	330.30	mtr.	31708.80
			330.30	111(1.	31700.00
	Supply and fixing in cement mortar welded hand railing made out of MS				
23	round or square bars, flats etc. for staircase or verandah as per design				
	complete in all respect (wooden or PVC hand railing to be paid extra) with				
	priming coat of red oxide.	9288.000	61.20	kg.	568425.60
24	Extra 10% for providing D type pipe head as top of hand railing	572.000	6.12	kg.	3500.64
	Providing and fixing steel gate, grating, and grills made of angles, tees,			- 0	•
	square bars, flats, or black pipe with holdfast and fittings complete as per				
25					
	design and drawing including cutting welding and fabrication with				064004.00
	priming coat of red oxide	5478.000	66.60	kg.	364834.80
26	Extra 10% if square, rectangular hollow tubelar sections are used or grill				
20	made by flats only	4659.000	6.66	kg.	31028.94
	Providing and fixing steel glazed doors windows and ventilator shutters of				
	standard rolled steel section (IS 1038-1983) joints mitred and welded with				
	steel lugs 13x3mm, 10cm. long embedded in cement concrete block				
	15x10x10cm. of 1:3:6 (1cement : 3 coarse sand : 6 graded stone aggregate				
	20mm nominal size) or with wooden plugs and screws or rawl plugs and				
27	screws with fixing clips or with bolts and nuts as required including				
21	providing and fixing of plain glass panes 4mm thick with cooper glazing				
	clips and special metal sash putty of approved make or metal beading with				
	screws complete including priming coat of approval steel primer,				
	excluding the cost of metal beading and other fitting except necessary				
	hinges of pivots steel handles peg stay etc. as required:				
<u> </u>		4			
	Windows side hung / Ventilators top or centre hung (openable)	19.200	2178.90	sqm	41834.88
	GALVANISED IRON SHEET ROOFING				
20	Grading roof for water proofing treatment with water proffing compound				
28					
28.1	Cement mortar 1:4 (1cement : 4 coarse sand)	232.585	3182.40	cum	740178.50
	KOTA STONE FLOORING				
	Kota stone slab flooring 25 mm thick over 20 mm (average) thick base laid				
	over and jointed with grey cement slurry mixed with pigment to match the				
29	shade of the slab including rubbing and polishing complete with base of				
	cement mortar 1:4 (1 cement: 4 coarse sand)				
	<u> </u>				
	For area of each slab from 2001 to 5000 Sq.Cm	2124.788	638.10	sqm	1355827.22
	Kota stone slabs 25 mm thick in risers of steps, skirting, dado and pillars			•	
	laid on 12 mm (average) thick cement mortar 1:3 (1 cement 3 coarse sand)				
20					
30	and jointed with grey cement slurry mixed with pigment to match the				
	shade of the slabs, including rubbing and polishing complete				
	For area of each slab from 2001 to 5000 Sqcm	106.876	625.50	sqm	66850.94
	SAND STONE FLOORING				
	Fine dressed & machine cut edges 30-35 mm thicksand stone flooring over				
	20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse				
31	sand) jointed grey cement slurry mixed with pigment to match the shade				
31					
	of stone complete as per design drawing and instruction of EI.				
	N. 1	1000.000	FEO.CC		FE0000 00
	Mandana stone	1000.000	550.80	sqm	550800.00

and the second process of the proces		Filling of our mounties of wood with combon mate of magnined beight			1	
versing and dressing, the surface by 50mm thick cement concrete 12.4 as per specification. CEMENT PLASTER Plaster on one warface on walls in cement sand mortar 15 including macking of joint etc. complete fine finish: 20mm thick. 30mm thick. 30mm thick cement plaster to ceiling of mix 1.3 (Icement : 3-fine sand) 40mm thick cement plaster to ceiling of mix 1.3 (Icement : 3-fine sand) 5492.709 5592.700 5692.700 570.500 580.3		Filling of sunk portion of roof with earthen pots of required height				
CEMENT PLASTER State on new surface on walls in cement sand mortar 1:6 including packing of point etc. complete fine finish: 20mm thick cement plaster to reiling of mix 1:3 (trement :3-fine sand) 5878,690 92.70 sqm 544954.56	32					
CREMENT PLASTER Signature CREMENT PLASTER Signature CREMENT PLASTER Signature CREMENT PLASTER Signature Sign				007.50		47046466
33 Baker on new surface on walls in coment sand mortur 1:6 including racking of point etc. complete fine finish; 20 mm thick. 34 6mm thick coment plaster to ceiling of mix 1:3 (teement :3-line sand) 35 Footsing and applying white coment based putty over plastered surface to prepare the surface even and smooth complete 35 Troviding and applying white coment based putty over plastered surface to prepare the surface even and smooth complete 36 NTERIOR FINISHING 37 Distempring with ol bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: 36 Troviding with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: 37 Troviding with plastic emulsion paint of approved brand and manufacture to give an even shade with the properties of the properties			530.699	886.50	cum	470464.66
20mm thick complete fine finish: 20mm thick complete fine finish: 30mm thick complete plaster to ceiling of mix 1:3 (Icement: 3-fine sand) 40mm thick complete plaster to ceiling of mix 1:3 (Icement: 3-fine sand) 542,709 67:30 sgm 370757:86 ROUGH CAST PLASTER 1 Providing and applying white coment based putty over plastered surface by prepare the surface even and smooth complete 1 NINIBROK PINISHING 30 Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: 1 Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: 1 Two or more coats on new work including preparation of base with primer, putty, lapve etc complete in all respect. 1 EXTERIOR RINBILING 2 Painting exterior surface of Wall with 100% accylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including preparation of base with sand papering, primer, putty, etc complete and respect. 2 New or more coats on new work. 2 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give an even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give and even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give and even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give and even shade: 3 Painting with synthetic enamel paint of approved brand and manufacture of give approved brand and manufac						
racking of joint etc. complete fine finish: 20mm thick commet plaster to ceiling of mix 1.3 (Leement: 3-fine sand) 30mm thick commet plaster to ceiling of mix 1.3 (Leement: 3-fine sand) 492,709 67.50 sqm 370757.86 ROUGH CASI PLASTIBE Tovokting and applying white cement based putty over plastered surface to prepare the surface even and smooth complete NI HAROM FINISHIMO 30mm thick prepare the surface even and smooth complete NI HAROM FINISHIMO Wall painting with plastic emolation point of approved brand and manufacture to give an even shade including all scalfolding: wall painting with plastic emolation point of approved brand and manufacture to give an even shade including all scalfolding: attribute to give an even shade including all scalfolding: ALIBROM FINISHIMO Parting section starting of Wall with 100% acrylic cotorior paint of approved brand and manufacture to give an even shade with two or more costs including preparation of base with sand papering primer, putty, etc complete in all respect. New Work PAINTING Parting section of the section of the provided brand and manufacture to give an even shade with two or more costs including preparation of base with sand papering primer, putty, etc complete in all respect. New Work PAINTING Providing of section of the provided brand and manufacture to give an even shade including preparation of base with sand papering within 50 metres lead as per direction of Engineer-in-charge. Unconsisting KCC. work manually/ by mechanical means including stacking of sections and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In committee of the providing of two components poly sulphide sealand containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealand including all bloom charges for sealing of exercised metred and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in	33					
mm thick cement plaster to ceiling of mix 1:3 (Leement: 3-fine sand) 80UCH CAST PLASTER 80UCH CAST PLASTER 87 Providing and applying white cement based putty over plastered surface to prepare the surface even and smooth complete 81NEBION FINISHING 810 Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all satifolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all satifolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade with two or more coats on new work including prepartion of base with primar, putty, lippy etc complete in all respect. Next PROTE NINISHING: Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc controlled and proved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc controlled and proved brand and manufacture to give an even shade with two or more coats including with synthetic enamel paint of approved brand and manufacture to give an even shade with two or more coats including with synthetic enamel paint of approved brand and manufacture to give an even shade with two or more coats and the special of the service of the standard good of underviceable material within 50 metres lead as per direction of Engineer-in-charge. 92677 579.60 cum 46180.79 1814 280 39.60 5qm 52045.49 Demolishing Erick work manually/ by mechanical means including all activities of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. 1814 280 39.60 5qm 52045.49 1814 280 39.60 5qm 520						
NOUCH CAST PLASTER NOUCH CAST PLASTER Toviding and applying white cement based putty over plastered surface to prepare the surface was and smooth complete. NITERIOR FINISHING Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: Two or more coats on new work including all scaffolding: Two or more coats on new work including prepartion of base with primer, putty, large exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade including all scaffolding: Two or more coats on new work including prepartion of base with primer, putty, large exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc. Painling exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc. Painling with synthetic enamel paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc. I wo or more coats on new work Demolishing KCCC. work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Foglineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of regarders on path such as a papering with even path of two components poly sulphide scalant containing solid contests, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide scalant including all labour charges for scaling of examination of expansion joint using with su			5878.690	92.70	sqm	544954.56
ROUGH CAST PLASTER Providing and applying white cement based putty over plastered surface to prepare the surface even and smooth complete. NTEROR FINISHING Distempering with old bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: Two or more costs on new work including grepartion of base with prime, putty, hippy text complete in all respect. EXTERIOR FINISHING Fainting scaetions surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more costs on new work including prepartion of base with sand papering, primer, putty, etc. FAINTING Fainting scaetions surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more costs including prepartion of base with sand papering, primer, putty, etc. New Work Palmiting with synthetic enamel paint of approved brand and manufacture to give an even shade with a providing stacking of sets of bars and disposal of unserviceable material within 30 metres lead as per direction of Engineer-in-charge. Demolishing RCC. work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 30 metres lead as per direction of Engineer-in-charge. Providing prick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 30 metres lead as per direction of Engineer-in-charge. Providing and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for scaling of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion point usin	34	6 mm thick cement plaster to ceiling of mix 1:3 (1cement : 3-fine sand)				
Toviding and applying white cement based putty over plastered surface to prepare the surface even and smooth complete NTERIOR INISHING Bistempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scarffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scarffolding: Two or more costs on new work including prepartion of base with primer, outst, input etc. complete in all respect. DYSTERIOR INISHING Pathing sections starting of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more costs and unduring prepartion of base with sand papering, primer, putty, etc. consolete in all respect. PAINTING Briting with synthetic enamel paint of approved brand and manufacture to give an even shade. Two or more costs on new work Demolshing, RCC. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolshing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION IOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming working development, of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand apapering with enery paper and filing with suitable mechanical means. The work includes racking mut cleaning of joints, sticking, debonding tupe on bottom of joint, applying primer on edges, susing masking tape on edges, providing of sealant and removal of masking tape inmediately after providing polye	J 1		5492.709	67.50	sqm	370757.86
INTERIOR INISERING. 36 Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: Two or more coats on new work including all scaffolding: Two or more coats on new work including all scaffolding: Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc consider in all respect. New Work Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc consider in all respect. New Work Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. PERANSION JOINT TREATMENT: EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved computible primer, for priming wertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and providing and limiting of two components sealing compound cleaning of joint, applying primer on edges, providing of Sealand and removal of making tape on edges, providing of Sealand and removal of making tape on edges		ROUGH CAST PLASTER				
INTERIOR INISERING. 36 Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: Two or more coats on new work including all scaffolding: Two or more coats on new work including all scaffolding: Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc consider in all respect. New Work Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc consider in all respect. New Work Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. PERANSION JOINT TREATMENT: EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved computible primer, for priming wertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and providing and limiting of two components sealing compound cleaning of joint, applying primer on edges, providing of Sealand and removal of making tape on edges, providing of Sealand and removal of making tape on edges	25	Providing and applying white cement based putty over plastered surface				
Disterpering with oil bound washable distemper of approved brand and manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: Two or more coats on new work including prepartion of base with primer, putty, inpry et complete in all respect. EXTERIOR FINSTING	33			64.80	sqm	627484.26
manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: 1 two or more coats on new work including prepartion of base with primer, putty, lippy et complete in all respect. EXTERIOR EINSHING Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc. complete in all respect. New Work PAINTING: Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 1 two or more coats on new work 1 wo or more coats on new work 1 bemolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. 1 bemolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. 1 In cement mortar. EXPANSION IOINT TREATMENT: Supplying and providing of two components sealing compound. 1 Cleaning solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. 1 Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking debonding tape on bottom of joint, applying primer on edges, providing and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical					•	
manufacture to give an even shade including all scaffolding: Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: 1 two or more coats on new work including prepartion of base with primer, putty, lippy et complete in all respect. EXTERIOR EINSHING Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc. complete in all respect. New Work PAINTING: Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 1 two or more coats on new work 1 wo or more coats on new work 1 bemolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. 1 bemolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. 1 In cement mortar. EXPANSION IOINT TREATMENT: Supplying and providing of two components sealing compound. 1 Cleaning solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. 1 Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking debonding tape on bottom of joint, applying primer on edges, providing and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical		Distempering with oil bound washable distemper of approved brand and				
Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade including all scaffolding: Ivo or more coats on new work including all scaffolding: Ivo or more coats on new work including prepartion of base with primer, putty, lippy etc complete in all respect. EXTERIOR FINISHING Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc consolete in all respect. PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demoilshing RCC. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demoilshing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming wertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joint saffer drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with enery paper and filling with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, providing of sealant including providing papering with enery paper and filling with suitable mechanical means. The work includes racking and ready of the components sealing compound. Cleaning and preparation of expansion joint sign that suitable mechanical means. The work includes racking and cleaning of join	36					
manufacture to give an even shade including all scalifolding: Two or more coats in new work including preparation of base with primer, putty, lippy etc complete in all respect. PartIREOR FINISHING: Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including preparation of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: I've or more coats on new work PERMINING Palonting with synthetic enamel paint of approved brand and manufacture to give an even shade: I've or more coats on new work PERMINING Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bras and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components scaling compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, stricking, lebonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant individual providing powerlylene coam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing another layer of poly sul		intuitate to give air even state including air scartolaing.				
manufacture to give an even shade including all scalifolding: Two or more coats in new work including preparation of base with primer, putty, lippy etc complete in all respect. PartIREOR FINISHING: Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including preparation of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: I've or more coats on new work PERMINING Palonting with synthetic enamel paint of approved brand and manufacture to give an even shade: I've or more coats on new work PERMINING Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bras and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components scaling compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, stricking, lebonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant individual providing powerlylene coam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing another layer of poly sul		Wall painting with plactic amulcion paint of approved brand and				
Two or more costs on new work including prepartion of base with primer, putty, hippy etc complete in all respect. EXTERIOR FINISHINGS Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc complete in all respect. New Work						
putty, lippy etc complete in all respect. EXTERIOR FINISHING Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more costs including preparation of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more costs on new work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more costs on new work Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more costs on new work Poemolishing R.C.C. work manually/ by mechanical means including stacking of steel bras and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant in joint. To vertical joint between RCC columns, bricks & stone massonry in size 40 minuting polyethylene foam back up or 40 5 mm and in a size and finally providing polyethylene foam back up or 40 5 mm and in a size and finally providing polyet						
Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including prepartion of base with sand papering, primer, putty, etc complete in all respect. New Work			10261 000	4E 00	6.222	04001E 7E
Painting exterior surface of Wall with 100% acrylic exterior paint of approved brand and manufacture to give an even shade with two or more coats including preparation of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam	<u> </u>		10301.999	43.90	sqin	042013./3
approved brand and manufacture to give an even shade with two or more costs including prepartion of base with sand papering, primer, putty, etc. complete in all respect. New Work PAINTING 38 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coals on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on bottom of joint, applying primer on edges, using masking tape on deges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal Joan) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. Foam and then depth over PE. Back up rod as per application procedure and direction of fineincer-in-charge. Providing and fixing 150 mm wide sheet c						
coats including prepartion of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Poemolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand apapering with enery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then the providing and fixing jst j mm wide sheet covering over expansion joints with into screws as per design to match the colour / shade of wall treatment. Aluminum flu						
coats including preparation of base with sand papering, primer, putty, etc complete in all respect. New Work PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. PANNION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Engineer-in-charve. Providing and fixing 100 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Alu	37					
New Work 748.000 77.40 sqm 577249.20 PAINTING Paliting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work 1314.280 39.60 sqm 52045.49 Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EPPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Enrineer-in-charre. Providing and laying 150 mm wide sheet cov						
PAINTING Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Demolshing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolshing brick work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolshing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on obottom of joint, applying primer on edges, using masking tape on edges, providing sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocool foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 12 mm depth, unrel. Back up rod as per application procedure and direction of Enrineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing						
Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work Two or more coats on new work			7458.000	77.40	sqm	577249.20
Two or more coats on new work Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mix width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To points in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Enmineer-in-charce. Providing and fiving frequired. Aluminum fluted strips 2 mm thick Providing and la						
Two or more coats on new work Two or more coats on new work Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mix width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To points in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Enmineer-in-charce. Providing and fiving frequired. Aluminum fluted strips 2 mm thick Providing and la	20	Painting with synthetic enamel paint of approved brand and manufacture				
Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mix with and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. Foam and then providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 30 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Engineer-in-charge. Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and Laying Reinforced Cement Concrete Pipe NP4 for c	38					
Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To into its inflooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Enrineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c			1314.280	39.60	sqm	52045.49
stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant and removal of masking tape immediately after providing sealant in pind. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineerin-charce. Providing and fixing 150 mm wide sheet covering over expansion joints with fron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
metres lead as per direction of Engineer-in-charge. 79.677 579.60 cum 46180.79 Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. 264.666 335.70 cum 88848.38 EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. 10 vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. 11 To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. 12 To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Enripeer-in-charge. 14 2 Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design t						
Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyetylene foam back up rod 25 mm dia size and finally providing polyetylene foam back up rod 25 mm dia size and finally providing polyetylene foam back up rod 25 mm dia size and finally providing polyetylene foam back up rod 25 mm dia size and finally providing polyetylene foam back up rod 25 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod 35 mm dia size and finally providing polyetylene foam back up rod	39					
Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Encineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and Laying reinforced cement concrete pipe NP4 for c		incress read as per unrection of Engliseer in charge.	79.677	579.60	cum	46180.79
stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with ron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and Laying Reinforced cement concrete pipe NP4 for c		Demolishing brick work manually/ by mechanical means including				
within 50 metres lead as per direction of Engineer-in-charge. In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and direction of Engineer-in-charce. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Sta3.360 270.00 R.Mtr. 146707.20						
In cement mortar. EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Encineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543,360 270.00 R.Mtr. 146707.20	40					
EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermoccal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Encineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Aluminum fluted strips 2 mm thick To providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		within 50 metres lead as per affection of Engineer in charge.				
EXPANSION JOINT TREATMENT: Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermoccal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE. back up rod as per application procedure and direction of Encineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Aluminum fluted strips 2 mm thick To providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		In cement mortar.	264.666	335.70	cum	88848.38
Supplying and providing of two components poly sulphide sealant containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c			201.000	000.70	cuiii	00010.00
containing solid contents, confirming to standard specification and approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. 41 Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. 41.1 To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
approved compatible primer, for priming vertical faces prior to application of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 270.00 R.Mtr. 146707.20 Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
of poly sulphide sealant including all labour charges for sealing of expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
expansion joints after drill mixing of two components sealing compound. Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
Cleaning and preparation of expansion joint using wire brush sand papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		expansion joints after drill mixing of two components sealing compound.				
papering with emery paper and filing with suitable mechanical means. The work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c	41					
work includes racking and cleaning of joints, sticking, debonding tape on bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
bottom of joint, applying primer on edges, using masking tape on edges, providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		• •				
providing of sealant and removal of masking tape immediately after providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
providing sealant in joint. To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		,				
To vertical joint between RCC columns, bricks & stone masonry in size 40 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
41.1 mm width and 12 mm depth, including providing back up material (Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 757.10 mtr. 334260.00 557.10 mtr. 334260.00 585.00 mtr. 315900.00 Foviding and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 70.00 R.Mtr. 146707.20						
(Thermocoal foam) if required. To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		,				
(Thermocoal foam) if required. 600.000 557.10 mtr. 334260.00 To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. 540.000 585.00 mtr. 315900.00 Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 270.00 R.Mtr. 146707.20 Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c	41.1	mm width and 12 mm depth, including providing back up material				
To joints in flooring, as per drawing with first layer of poly sulphide sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c		(Thermocoal foam) if required.	600.000	557.10	mtr.	334260.00
sealant in size 20 mm width and 10 mm depth over PE Foam and then providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
providing polyethylene foam back up rod 25 mm dia size and finally providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
providing another layer of poly sulphide sealant in size 20 mm width and 10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c	41.2	_				
10 mm depth over P.E. back up rod as per application procedure and direction of Engineer-in-charge. Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c	41.2					
direction of Engineer-in-charge. 540.000 585.00 mtr. 315900.00 Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 270.00 R.Mtr. 146707.20 Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
Providing and fixing 150 mm wide sheet covering over expansion joints with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick 543.360 270.00 R.Mtr. 146707.20 Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c				585.00	mtr.	315900.00
with iron screws as per design to match the colour / shade of wall treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
treatment. Aluminum fluted strips 2 mm thick Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c	42					
Aluminum fluted strips 2 mm thick 543.360 270.00 R.Mtr. 146707.20 Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c						
Providing and Laying Reinforced Cement Concrete Pipe NP4 as Providing and laying reinforced cement concrete pipe NP4 for c			543 360	270.00	R M+r	146707 20
Providing and laying reinforced cement concrete pipe NP4 for c	-			∠/ U.UU	13.19111.	170/0/.20
	43					
1000 Hilli dia 500.000 4230.00 K.Mtr. 2115000.00			E00.000	4000.00	D Mr	2115000.00
	•	1000 Hill ala	500.000	4230.00	K.IVITT.	Z113UUU.UU

			Tota	l Amount	23,567,617.62
	Diameter 900 mm	30.000	569.70	R.Mtr.	17091.00
46	Supply & fixing Pre-cast RCC Rinngs at the mouth of recharge shaft of M20 mix with 40 mm thickness				
	RAIN WATER HARVESTING				
	for drain Opeining Size 1201 to 1500 mm Standard Drain Cover Size $1800 \text{mm} \times 600 \text{mm} \times 75 \text{mm}$	97.200	1075.50	sqm	104538.60
45	designed for side drain for class "B" Road loading duly marked on cover with adequate steel reinforcement having thickness 50 mm to 75 mm anti corrosive bitumen painted M.S. plate Rim and on M.S. lifting hooks additives & admixture like plasticizer shrinkage resistance compound abrasion resistant as per approved drawing and design complete in all respect.				
	(20 x 25) / 2 x 30 cm Supply &fixing of Fiber reinforced Ferro cement drain cover (light duty)		315.00	R.Mtr.	630000.00
44	60 cm length over 20 mm thick base of cement mortar 1:6 including jointing earth work, painting & jointing with cement mortar 1:4 of size		215.00	P.M.	(20000 00
	Supply & fixing of M-20 grade precast cement concrete Kerb or Dand upto				

Executive Engineer (Project-II) JDA, Jaipur